


**ASTM D178 SWITCHBOARD MATTING**

products are tested and certified to the most rigorous industry standards. Every roll is proof tested at the specified voltage per class over the entire surface. Single piece rolls are guaranteed.

This nonconductive matting is engineered and tested to protect workers from shock in high voltage applications within product specifications.

**TYPE I, CLASS 2 CORRUGATED**

Recommended for distribution boards, switchgear, substations, transformers, generators, and electrical workbenches.



**PROVEN INDUSTRIAL MATTING SOLUTIONS**

When it comes to quality matting, Westlake Dimex is a name you can count on for dependable performance. Westlake Dimex Matting Products are the result of years of research, testing, and development. We lead the industry in product quality, availability, and customer support. No matter what your matting needs may be, Westlake Dimex can deliver the perfect solution.

**TYPE I, CLASS 2 CORRUGATED SWITCHBOARD MATTING (ASTM)**

**TYPE I, CLASS 2 CORRUGATED**

Part No.	Color/Finish	Thickness	Width	Length	Weight
5V-014-24-75DC	Black	1/4"	24"	75'	170
5V-014-36-75DC	Black	1/4"	36"	75'	260
5V-014-48-75DC	Black	1/4"	48"	75'	340

**Tested at 20,000 VAC Recommended Maximum Use Voltage: 17,000 VAC**

The type defines the compound that is used to manufacture the switchboard matting according to the ASTM D178 specification. Westlake Dimex manufactures both Type I and Type II.

*Dimex<sup>®</sup> Switchboard Matting (ASTM) is available in:*

- *Type I, Class 2 Corrugated*
- *Type II, Class 1 Corrugated*
- *Type II, Class 2 Corrugated*
- *Type II, Class 2 Diamond Plate*
- *Type II, Class 3 Corrugated*
- *Type II, Class 4 Corrugated*